

Date _____

Name _____

Client _____



Project Name _____

Quote# _____

Type/Quantity _____

GRID IN TRIMLESS 1 HP 303027
202 684 20122

[Weblink](#)



Cutout shape/size:	KIT mm
Recessed depth:	180 mm
Available colors:	WHITE-BLACK (202 684 20122 W-B)
ADJUSTABLE 0°- 20°/340°	
INCL.1 x POWERLED WHITE 26W / CRI>80 / 3000K / 3000lm	
INCL.1 x REFLECTOR FL-27°	
EXCL.LED POWER SUPPLY 600mA-DC	
LED Technics:	Light source: 3000 lm // 26 W // 115 lm/W Luminaire: 2155 lm // 30 W // 72 lm/W
Class:	III
Weight:	2.1 KG
Protection level:	IP20
Minimum distance:	n.a.
Accessories:	HONEYCOMB 87 LINEAR SPREAD LENS 87 SPREAD LENS 87 SOFTENING LENS 87 GLASS SBL 87
Requirements:	GRID IN TRIMLESS 1 MOUNTING KIT HP LED POWER SUPPLY 600-700mA-DC / 38W LED POWER SUPPLY 600-700mA-DC / 35W DIM2

For detailed installation instructions, please consult the manual. [202 684 20122 HAND.pdf](#)


GRID IN TRIMLESS 1 HP 303027

202 684 20122

Related references


LED POWER SUPPLIES

[Weblink / Specs sheet](#)



LED POWER SUPPLY 600-700mA-DC / 35W DIM2
300 90 66 ED2
220-240V / 50-60Hz
Number of luminaires: 1

[Weblink / Specs sheet](#)




LED POWER SUPPLY 600-700mA-DC / 38W
300 90 66
220-240V / 50-60Hz
Number of luminaires: 1

Related references

MOUNTING KITS

[Weblink / Specs sheet](#)



GRID IN TRIMLESS 1
MOUNTING KIT HP
202 61 95 01 HP

Related references

LIGHT ALTERING DEVICES


[Weblink / Specs sheet](#)



Ø87

GLASS SBL 87
201 01 05

[Weblink / Specs sheet](#)



Ø87

HONEYCOMB 87
201 01 01


[Weblink / Specs sheet](#)



Ø87

LINEAR SPREAD LENS 87
201 01 02


[Weblink / Specs sheet](#)



Ø87

SOFTENING LENS 87
201 01 04

[Weblink / Specs sheet](#)



Ø87

SPREAD LENS 87
201 01 03

GRID IN TRIMLESS 1 HP 303027
202 684 20122

Project picture

