



USA / deltalight.us / +1(954) 677 9800
 Canada / deltalight.ca / +1(905) 813 6130

Date

Name

Client

Project Name

Quote#

Type/Quantity

Features

Powder coated steel construction, aluminum die cast cooler Fully adjustable gimble Pre-installed snap-in connector

Application

For ambient lighting Commercial, retail, and hospitality spaces

Dimming Options

Refer to housing or power supply spec sheet.

Listings





Specification Sheet

GRID IN TRIMLESS 2 HP 303027

6 202 684 20222

[Weblink](#)



Available colors: WHITE-BLACK (6 202 684 20222 W-B)

ADJUSTABLE 0° - 20°/340°

INCL.2 x POWERLED WHITE 26W / CRI>80 / 3000K / 3000lm

INCL.2 x REFLECTOR FL-27°

EXCL.LED POWER SUPPLY 600mA-DC

LED Technics: Light source: 6000 lm // 51 W // 115 lm/W
 Luminaire: 4311 lm // 60 W // 72 lm/W

Class2Only Yes
 Ada N.a.

Weight: 7.3 LBS
 Protection level: IP20 - suitable for damp locations
 Minimum distance: n.a.

Accessories: HONEYCOMB 87
 LINEAR SPREAD LENS 87
 SPREAD LENS 87
 SOFTENING LENS 87
 GLASS SBL 87

Requirements STANDARD:



NON IC PLASTERFRAME

For detailed installation instructions, please consult the manual. [6 202 684 20222 HAND.pdf](#)

GRID IN TRIMLESS 2 HP 303027
6 202 684 20222






Related references

NON IC PLASTERFRAME

<p><u>Weblink / Specs sheet</u></p>  <p>NIC L 600mA-DC 2x40W ED1 120V GI 2 MTK HP 6 202 0357 62 11</p>	<p><u>Weblink / Specs sheet</u></p>  <p>NIC L 600mA-DC 2x40W Ed1 277V GI 2 MTK HP 6 202 0357 62 21</p>
---	---

Related references

LIGHT ALTERING DEVICES

<p><u>Weblink / Specs sheet</u></p>  <p>Ø87mm Ø3"-7/16</p> <p>GLASS SBL 87 201 01 05</p>	<p><u>Weblink / Specs sheet</u></p>  <p>Ø87mm Ø3"-7/16</p> <p>HONEYCOMB 87 201 01 01</p>	<p><u>Weblink / Specs sheet</u></p>  <p>Ø87mm Ø3"-7/16</p> <p>LINEAR SPREAD LENS 87 201 01 02</p>	<p><u>Weblink / Specs sheet</u></p>  <p>Ø87mm Ø3"-7/16</p> <p>SOFTENING LENS 87 201 01 04</p>
<p><u>Weblink / Specs sheet</u></p>  <p>Ø87mm Ø3"-7/16</p> <p>SPREAD LENS 87 201 01 03</p>			